

Linear Dimensions

Permissible deviations in mm for ranges in nominal lengths	Tolerance class designation (description)			
	f (fine)	m (medium)	c (coarse)	v (very coarse)
0.5 up to 3	±0.05	±0.1	±0.2	–
over 3 up to 6	±0.05	±0.1	±0.3	±0.5
over 6 up to 30	±0.1	±0.2	±0.5	±1.0
over 30 up to 120	±0.15	±0.3	±0.8	±1.5
over 120 up to 400	±0.2	±0.5	±1.2	±2.5
over 400 up to 1000	±0.3	±0.8	±2.0	±4.0
over 1000 up to 2000	±0.5	±1.2	±3.0	±6.0
over 2000 up to 4000	–	±2.0	±4.0	±8.0

External Radius and Chamfer Heights

Permissible deviations in mm for ranges in nominal lengths	Tolerance class designation (description)			
	f (fine)	m (medium)	c (coarse)	v (very coarse)
0.5 up to 3	±0.2	±0.2	±0.4	±0.4
over 3 up to 6	±0.5	±0.5	±1.0	±1.0
over 6 up to 30	±1.0	±1.0	±2.0	±2.0

Angular Dimensions

Permissible deviations in degrees & minutes for ranges in nominal lengths	Tolerance class designation (description)			
	f (fine)	m (medium)	c (coarse)	v (very coarse)
up to 10	±1°	±1°	±1°30'	±3°
over 10 up to 50	±0°30'	±0°30'	±1°	±2°
over 50 up to 120	±0°20'	±0°20'	±0°30'	±1°
over 120 up to 400	±0°10'	±0°10'	±0°20'	±0°30'
over 400	±0°5'	±0°5'	±0°10'	±0°20'

Straightness and Flatness

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
up to 10	0.02	0.05	0.1
over 10 up to 30	0.05	0.1	0.2
over 30 up to 100	0.1	0.2	0.4
over 100 up to 300	0.2	0.4	0.8
over 300 up to 1000	0.3	0.6	1.2
over 1000 up to 3000	0.4	0.8	1.6

Perpendicularity

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
up to 100	0.2	0.4	0.6
over 100 up to 300	0.3	0.6	1
over 300 up to 1000	0.4	0.8	1.5
over 1000 up to 3000	0.5	1.0	2

Angular Dimensions

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
up to 100	0.5	0.6	0.6
over 100 up to 300	0.5	0.6	1
over 300 up to 1000	0.5	0.8	1.5
over 1000 up to 3000	0.5	1	2

Circule Run-Out

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
	0.1	0.2	0.5